



- 78-Spring
- 79-Fire-rated hatch
- 80-Tread
- 86-Hinge
- 88-Side bracket
- 93-Stile end
- 94-Stringer (ladder side element)
- 686-Architraves LXL-PVC FAKRO
- 714-Fire-resistant sealant
- 715-Rock wool ( $\rho=60\text{kg/m}^3$ )

P	S	E
Hatch board movement after opening	Tread width	Tread length
[cm]	[cm]	[cm]
5	8	34

LOFT LADDER LMF 60											
H Room height	H. Min. Room height	A Width ceiling opening dimensions	B Length ceiling opening dimensions	K Folded loft ladder height	R Swing space	C Distance after ladder unfolding	T Box height	WxL Outside box dimensions	MxN Inside box dimensions	G Distance between treads	
[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	[cm]	
280	233	60	120	39	156	125	22.5	58x118	54x114	25	
		70	120					68x118	64x114		
		70	130					68x128	64x124		
		70	140					68x138	64x134		
		86	130					84x128	80x124		
305	234	70	130		167	135		68x128	64x124		
		70	140					68x138	64x134		
		86	130					84x128	80x124		

FAKRO®



Warning! The present drawing is for informational-demonstrative purposes only and as such cannot constitute a basis for performance. All dimensions presented in this drawing should be verified on site. Because of the fact that the drawing is a schematic one, FAKRO shall not assume any responsibility for the actual installation quality. This drawing is FAKRO's property and cannot be published or used publicly without our written consent.

Technical drawing:

The LMF60 Loft Ladder

Height 280-305 cm

FORMAT:

A4

SCALE:

1:25

DATE:

01.2022