

TECHNICAL SPECIFICATION

ATTIC LADDER LMP

I. APPLICATION

Folding section attic ladder **LMP** allows access to the attic space, even in very high rooms, while maintaining maximum comfort and safety of use. Supported room height range from 9'10" to 12'.

II. STRUCTURE							
No.	Element	Description					
1	Hatch	insulated, sandwich type, thickness: 1¾". thermal insulation thickness: 1½".					
2	Frame	pinewood. height: 71⁄8" seal: 1x					
3	Ladder	metal ladder width: 15" stringer height: 31%" Distance between stepss: 91⁄2".					
4	Steps	metal, equipped with anti-slip profile. step width: 31/8" length: 133/8"					
5	Standard Accessories	Plastic ends Handrail with unloading mechanism. Lightweight aluminum telescopic rod to open the hatch.					

III. DIMENSIONS					
No.	Rough Opening	Room height			
1	22,5" x 56,5"				
2	25" x 56,5"	9′10″ – 12′			
3	30" x 56,5"				

IV. TECHNICAL PARAMETERS						
Maximum loading	375 lbs					
Heat transfer coefficient	R-value: 5.2					

V. COMPATIBLE ACCESSORIES						
Ladder balustrade LXB-U	The balustrade is available in one standard size 30"x54" for all attic ladders.					
Wooden trim LXL-W	The trims are available in size 30"x56,5" for smaller sizes have to be cut.					
PCV trim LXL-PVC	The trims are available in size 30"x56,5" for smaller sizes have to be cut.					
Box extension LXN	The standard box height is 4". While ordering the LXN please provide ladder type and size.					
Upper hatch LXW	The height of the upper hatch box is 734".					
Installation brackets LXK	Maximum ceiling 15% "					



VI. ASSEMBLY INFORMATION

The **LMP** attic ladder is delivered to the customer fully assembled, it requires only screwing side elements of the supports which for transport purposes are unscrewed. The length of the last segment should be cut on-site to suit to existing ceiling height. Installation of the product must be carried out in accordance with the included fitting instructions.

VII.DETAILED DIMENSIONS



LMP		22½ x 56½	25 x 56½	30 x 56½
Manufacturer's part number:		869331	869332	869333
Ceiling height		9′10″ - 12′		
Rough opening		22 ½" x 56 ½"	25" x 56 ½"	30" x 56 ½"
Outside frame dimensions		22" x 56"	24 ½" x 56"	29 ½" x 56"
Internal frame dimensions		20 ½" x54 ¾"	22 %" x54 %"	28" x 54 3%"
Projection R		77 1/8"		
Landing space (57 1/8"		
Folded ladder height K		12 %"		
Frame height		7 1/8"		
Approx. Weight (lbs)		102	108	114